Registered ISO 9001:2000

T E C H N I C A L D A T A

FV-340WP-90-MP26 (Part # 3035sl)
WHITE FLEXIBLE VINYL-PERMANENT ADHESIVE

FV-340WP-90-MP26 GRAPHIC

DESCRIPTION

FV-340WP-90-MP26 is a 3.4-mil white flexible vinyl designed for label applications where an general purpose acrylic adhesive is required. This product is coated with our MP26 permanent acrylic adhesive, which is a high tack acrylic adhesive that has excellent adhesion to a wide variety of surfaces. The MP26 exhibits excellent resistance to UV light, heat, humidity, most solvents and mild plasticizers. As with all high performance applications, thorough evaluation is required prior to use.

TAPE CONSTRUCTION

FACE MATERIAL	3.4MIL WHITE FLEX VINYL
ADHESIVE (MP26)	**1.0**MIL
RELEASE LINER	90 LB. PC KRAFT

TYPICAL ADHESIVE PERFORMANCE DATA

PEEL ADHESION (PSTC-101)	
15 MINUTE APPLIED (oz./in.)	50-60
24 HOUR APPLIED (oz./in.)	85-95
SHEAR ADHESION (PSTC-107)	
1" X 1", 1,000 GRAMS, 72 DEGREES F (Hours)	24+
MINIMUM APPLICATION TEMPERATURE	50 DEGREES F

NOTE: **Performance data indicates average production values from stainless steel and should not be used for minimum specification values. It is required that the converter determines suitability of tape prior to use.**

DATE: 12/5/07 igc

The information contained herein is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

206 East Division Street • Mount Juliet, Tennessee 37122 • (615) 754-9797 • Fax (615) 758-6200