



Registered ISO 9001:2000

**T E C H N I C A L      D A T A**

**TC-2BRUSH-90-MP29 (Part # 3148sl)  
2MIL BRUSH SILVER POLYESTER-PERMANENT ADHESIVE**

**DESCRIPTION**

TC-2BRUSH-90-MP29 is a 2 mil brush silver, top-coated polyester film designed for high quality decal applications. The 2Mil polyester is top-coated for improved ink adhesion for a wide variety of screen, UV, offset and letterpress inks. This product is coated with our MP29 permanent acrylic adhesive, which bonds well to high surface energy materials and exhibits excellent resistance to UV light, heat, humidity, most solvents and mild plasticizers.

**TAPE CONSTRUCTION**



**TYPICAL ADHESIVE PERFORMANCE DATA**

**PEEL ADHESION (PSTC-101)**

15 MINUTE APPLIED (oz./in.)	50-60
24 HOUR APPLIED (oz./in.)	75-85

**SHEAR ADHESION (PSTC-107)**

1" X 1", 1,000 GRAMS, 72 DEGREES F (Hours)      24+

**MINIMUM APPLICATION TEMPERATURE**      50 DEGREES F

**NOTE:** Performance data indicates average production values from stainless steel and should not be used for minimum specification values. It is required that the converter determines suitability of tape prior to use.

**DATE:** 10/11/05 igc

The information contained herein is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

TC-2BRUSH-90-MP29 GRAPHIC