Registered ISO 9001:2008

T E C H N I C A L D A T A

A902-2PT (Part # 2327sl)

ANTI-SQUEAK BLACK FLOCKED FABRIC PSA

A902-2PT INDUSTRIAL

DESCRIPTION

A902-2PT is a high quality 1.0mm black flocked fabric designed for demanding automotive interior anti-squeak applications. A902-2PT is coated with a heavy mass of high performance acrylic adhesive, which exhibits excellent adhesion to a wide variety of substrates and has resistance to heat, humidity, solvents and mild plasticizers. This product is also available on a 78# Densified Kraft liner. The flocked fabric was specifically designed to meet the performance requirements for GM6420M Type 1B and Chrysler PF-10770.

TAPE CONSTRUCTION

FACE MATERIAL	1.0mm BLACK FLOCKED FABRIC
ADHESIVE (MP27)	4.25MIL
RELEASE LINER	2.0MIL POLYESTER LINER

TYPICAL ADHESIVE PERFORMANCE DATA

PEEL ADHESION (PSTC-101)

Substrate: PP	15 MIN APPLIED (oz./in.)	45-55
	24 HR APPLIED (oz./in.)	45-55
Substrate: SS	15 MIN APPLIED (oz./in.)	45-55
	24 HR APPLIED (oz./in.)	55-65

SHEAR ADHESION (PSTC-107)

1" X 1", 1,000 GRAMS, 72 DEGREES F (Hours)	24+
MINIMUM APPLICATION TEMPERATURE	50 DEGREES F

NOTE: Performance data indicates average production values from stainless steel and should not be used for minimum specification values. It is required that the converter determines suitability of tape prior to use.

DATE: 11/30/10 igc

The information contained herein is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

206 East Division Street • Mount Juliet, Tennessee 37122 • (615) 754-9797 • Fax (615) 758-6200