



Registered ISO 9001:2008

T E C H N I C A L D A T A

Part: PPM-300GW-50 (3361sl)
2.3MIL WHITE POLYPROPYLENE LABEL STOCK

DESCRIPTION

PPM-300GW-50 is a 2.3mil corona-treated glossy white polypropylene film coated with our modified acrylic emulsion adhesive. The adhesive exhibits very good tack and peel adhesion in addition to moderate shear strength and has good resistance to heat, humidity, UV light, mild solvents and plasticizers. PPM-300GW-50 is recommended for use on difficult applications to low energy surfaces plastics, including battery labels. The release liner is an easy-release 50lb. bleached densified-kraft.

TAPE CONSTRUCTION



TYPICAL PERFORMANCE DATA

PEEL ADHESION (PSTC-101)	
5 MINUTE APPLIED PP PANEL (oz./in.)	55-70
POLYPROPYLENE DYNE LEVEL	40
SHEAR ADHESION (PSTC-107)	
1" X 1", 1,000 GRAMS, 72 DEGREES F (Hours)	5+
MINIMUM APPLICATION TEMPERATURE	50 DEGREES F
NO LOAD APPLIED, SERVICE TEMPERATURE RANGE	
	-35 TO 160 DEGREES F CONTINUOUS

NOTE: Performance data indicates average production values from stainless steel and should not be used for minimum specification values. It is required that the converter determines suitability of tape prior to use.

DATE: 11/21/11 igc

The information contained herein is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

206 East Division Street • Mount Juliet, Tennessee 37122 • (615) 754-9797 • Fax (615) 758-6200

PPM-300GW-50 GRAPHIC